

21—NEOTECTONIC AND EARTHQUAKE-HAZARD FEATURES

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
21.1	Earthquake epicenter, magnitude 7.5 or larger		color 100% violet outer circle diameter 7.0 mm; inner circle diameter 5.75 mm; linewidth .25 mm inner dot diameter 4.5 mm	The type of scale used for measuring earthquakes should be noted. May also be shown in black or other colors.
21.2	Earthquake epicenter, magnitude 7–7.49		color 100% violet dot diameter 4.25 mm	
21.3	Earthquake epicenter, magnitude 6.5–6.99		color 100% violet inner dot diameter 2.375 mm circle diameter 4.0 mm; linewidth .25 mm	
21.4	Earthquake epicenter, magnitude 6–6.49		color 100% violet dot diameter 2.25 mm	
21.5	Earthquake epicenter, magnitude 5.5–5.99		color 100% violet circle diameter 2.25 mm; linewidth .25 mm	
21.6	Earthquake epicenter, magnitude 4–5.49		color 100% violet circle diameter 1.4 mm; linewidth .225 mm	
21.7	Earthquake epicenter, magnitude less than 4		color 100% violet circle diameter .875 mm; linewidth .2 mm	
21.8	Fault-plane or focal-mechanism diagram for vertical, down-to-the-left offset along north-striking, vertical fault—Black quadrant indicates region of compression		size may vary 	Note that two types of fault motion and (or) two different fault-plane orientations could be represented by the same focal-mechanism diagram. For example, the focal-mechanism diagram that shows right-lateral strike-slip offset along a north-striking, vertical fault (ref. no. 21.9) could also show left-lateral strike-slip offset along an east-west-striking, vertical fault.
21.9	Fault-plane or focal-mechanism diagram for right-lateral strike-slip offset along north-striking, vertical fault—Black quadrants indicate regions of compression			
21.10	Fault-plane or focal-mechanism diagram for left-lateral strike-slip offset along north-striking, vertical fault—Black quadrants indicate regions of compression			
21.11	Fault-plane or focal-mechanism diagram for normal, down-to-the-left offset along north-striking, west-dipping (at 45°) fault—Black quadrants indicate regions of compression			
21.12	Fault-plane or focal-mechanism diagram for normal, down-to-the-left offset along northwest-striking, southwest-dipping (at 30°) fault—Black quadrants indicate regions of compression			
21.13	Fault-plane or focal-mechanism diagram for reverse, left-side-up offset along north-striking, west-dipping (at 45°) fault—Black quadrant indicates region of compression			
21.14	Fault-plane or focal-mechanism diagram for reverse, left-side-up offset along northwest-striking, southwest-dipping (at 60°) fault—Black quadrant indicates region of compression			
21.15	Fault-plane or focal-mechanism diagram for oblique reverse, left-side-up offset along northwest-striking, southwest-dipping (at 60°) fault—Black quadrants indicate regions of compression			
21.16	Outer limit of subsidence caused by shock—Identity and existence certain, location accurate. Hachures point into subsided area		all linewidths .275 mm 	May also be shown in violet or other colors.
21.17	Outer limit of subsidence caused by shock—Identity or existence questionable, location accurate. Hachures point into subsided area			
21.18	Outer limit of subsidence caused by shock—Identity or existence certain, location approximate. Hachures point into subsided area			
21.19	Outer limit of subsidence caused by shock—Identity or existence questionable, location approximate. Hachures point into subsided area			
21.20	Outer limit of subsidence caused by shock—Identity or existence certain, location inferred. Hachures point into subsided area			
21.21	Outer limit of subsidence caused by shock—Identity or existence questionable, location inferred. Hachures point into subsided area			
21.22	Outer limit of subsidence caused by shock—Identity and existence certain, location concealed. Hachures point into subsided area			
21.23	Outer limit of subsidence caused by shock—Identity or existence questionable, location concealed. Hachures point into subsided area			

*For more information, see general guidelines on pages A-i to A-v.

21—NEOTECTONIC AND EARTHQUAKE-HAZARD FEATURES (continued)

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
21.24	Rim crest or crater with rim, formed by shock or sand blowouts—Identity and existence certain, location accurate. Hachures point into crater		all lineweights .2 mm 	May also be shown in violet or other colors.
21.25	Rim crest or crater with rim, formed by shock or sand blowouts—Identity or existence questionable, location accurate. Hachures point into crater			
21.26	Rim crest or crater with rim, formed by shock or sand blowouts—Identity or existence certain, location approximate. Hachures point into crater		3.5 mm 	
21.27	Rim crest or crater with rim, formed by shock or sand blowouts—Identity or existence questionable, location approximate. Hachures point into crater			
21.28	Rim crest or crater with rim, formed by shock or sand blowouts—Identity and existence certain, location concealed. Hachures point into crater		1.25 mm 	
21.29	Rim crest or crater with rim, formed by shock or sand blowouts—Identity or existence questionable, location concealed. Hachures point into crater			
21.30	Sinkhole or crater without rim, formed by shock—Identity and existence certain, location accurate. Hachures point into sinkhole		all lineweights .2 mm 	
21.31	Sinkhole or crater without rim, formed by shock—Identity or existence questionable, location accurate. Hachures point into sinkhole			
21.32	Sinkhole or crater without rim, formed by shock—Identity or existence certain, location approximate. Hachures point into sinkhole		3.5 mm 	
21.33	Sinkhole or crater without rim, formed by shock—Identity or existence questionable, location approximate. Hachures point into sinkhole			
21.34	Sinkhole or crater without rim, formed by shock—Identity or existence certain, location concealed. Hachures point into sinkhole		.5 mm 	
21.35	Sinkhole or crater without rim, formed by shock—Identity or existence questionable, location concealed. Hachures point into sinkhole			
21.36	Fissures or cracks, formed in ground by earthquake		lineweights .2 mm 	
21.37	Fissures and sand and (or) other material ejected during earthquake		lineweights .3 mm 	

*For more information, see general guidelines on pages A-i to A-v.